



WerkMaster Chemicals Inc.
1448 Charlotte Road, North Vancouver, BC, Canada V7J 1H2
tel: 604.629.8700 | fax: 604.990.9538 | www.werkmaster.com

DESCRIPTION

Aliphatic 2 part Urethane floor coating.

INTENDED USE

- For concrete floors in conjunction with the WerkMaster Ultra Floor System where extreme chemical resistance is required.

PRODUCT FEATURES

- Extreme chemical, oil and acid resistance
- Very high gloss
- Extremely durable-no stripping

PHYSICAL PROPERTIES

- Flash Point N/A
- Viscosity Info not available
- Colour Info not available
- Type of Solids Info not available
- Boiling Point..... 999° – 220°F
- Odour Info not available

LIMITATIONS OF USE

For industrial/professional use only.

ORDERING INFORMATION

Call WerkMaster toll free:
1.866.373.WERK

SURFACE PREPARATION

Floor must be clean and dry and free from all other sealers other than UltraBlock.

Application Instructions: apply 1 thin even coat using a pump up sprayer and a microfiber applicator at a rate of 500-750 sq/ft per gallon.

MIXING INSTRUCTIONS

- Add Part B to one gallon of Part A and mix thoroughly for 30 seconds.
- Allow mixture to stand for 30 minutes before applying.
- DO NOT cover mixed product as it generates CO2.
- DO NOT expose Part B to air until ready to mix.

APPLICATION INSTRUCTIONS

Apply 1–2 medium coats of UltraGuard Plus.

STORAGE

DO NOT allow to freeze.

COMPLIANCES

VOC 98gm/L Calif. Compliant.

CHEMICAL RESISTANCE

Extreme resistance to abrasion, acids, oils, alcohols, detergents and solvents.

PRECAUTIONS

Please refer to the appropriate material safety data sheet (MSDS) prior to using this product.

For technical assistance, please call 1-866-373-WERK

FOR INDUSTRIAL/PROFESSIONAL USE ONLY

Keep containers closed when not in use and upright to prevent leakage. DO NOT take internally. Wash hands after using and before eating. Keep out of reach of children. Dispose of according to law and local regulations.

WARRANTY

WerkMaster Chemicals Inc. will replace any material found to be defective. Because the storage, handling and application of this material is beyond our control, we can accept no liability for the results obtained.

DISCLAIMER

All information on this data sheet is based on laboratory testing and is not intended for design purposes. WerkMaster Chemicals Inc. makes no representations or warranties of any kind concerning this data.

Taking it to the Wall!