

ULTRApreCut™

WerkMaster Chemicals Inc.

1448 Charlotte Road, North Vancouver, BC, Canada V7J 1H2

tel: 604.629.8700 | fax: 604.990.9538 | www.werkmaster.com

DESCRIPTION

Organic acid replacement concrete safety etcher and cleaner.

INTENDED USE

- Etching hard concrete floors before grinding.
- Remove insoluble salts like calcium and magnesium.
- Remove concrete from tools.
- Clean and etch floors before applying coatings.

PRODUCT FEATURES

- Safe organic replacement for traditional acids.
- Non-fuming, will not harm skin.
- Safe to use on aluminum, copper, stainless steel, painted surfaces, tile and grout.
- Odourless, does not require neutralizing.
- Revolutionary new acid alternative cleans with industrial strength.
- 100% Biodegradable and environmentally safe.

PHYSICAL PROPERTIES

- Flash Point Not flammable
- Viscosity Water-Like
- Colour Clear
- Type of Solids Info not available
- Boiling Point 212°F (100°C)
- Odour Mild
- pH 1.6 of 1/10 wt/wt solution in soft water

LIMITATIONS OF USE

For industrial/professional use only.

ORDERING INFORMATION

Call WerkMaster toll free:
1.866.373.WERK

SURFACE PREPARATION

Remove excessive dust, dirt and debris by vacuuming, sweeping or dust mopping.

MIXING INSTRUCTIONS

- For etching use full strength.
- Dilute 1:1 for general cleaning (one part Ultra Pre-Cut to one part water)
- Rinse and pick up.
- No neutralizing required.

APPLICATION INSTRUCTIONS

Dispense Ultra Pre-Cut into a pump up sprayer or sprinkling can and apply generously and evenly over the floor. Let product dwell on the surface for at least 10 minutes. If grinding the floor, begin grinding before product has dried on the surface. For cleaning purposes, scrub and rinse the area being worked on. No neutralizing required, if product dries onto the surface simply re-apply and grind, scrub or rinse away.

STORAGE

Do not allow to freeze. Store in a cool, dry, well ventilated place.

COMPLIANCES

Product does not contain any volatile organic compounds.

CHEMICAL RESISTANCE

N/A

PRECAUTIONS

Avoid contact with oxidizers. Contact with hypochlorite's such as chlorine bleach, sulphides or cyanides will liberate toxic gases. Please refer to the appropriate material safety data sheet (MSDS) prior to using this product.

For technical assistance, please call 1-866-373-WERK
FOR INDUSTRIAL/PROFESSIONAL USE ONLY

Keep containers closed when not in use and upright to prevent leakage. DO NOT take internally. Wash hands after using and before eating. Keep out of reach of children. Dispose of according to law and local regulations.

WARRANTY

WerkMaster Chemicals Inc. will replace any material found to be defective. Because the storage, handling and application of this material is beyond our control, we can accept no liability for the results obtained.

DISCLAIMER

All information on this data sheet is based on laboratory testing and is not intended for design purposes. WerkMaster Chemicals Inc. makes no representations or warranties of any kind concerning this data.

Taking it to the Wall!